

According to IEC 60947-3, EN 60947-3, VDE 0660 part 107



Rated Thermal Current I _U /I _{th} /I _{the}				A	63
Rated Insulation Voltage U _I ¹				V	690
Rated Impulse Withstand Voltage U _I mp				kV	6
Rated Operational Current I _e					
AC-21A	Switching of resistive loads, including moderate overloads			A	63
AC-22A	Switching of combined resistive or low inductive loads including moderate overloads		220 V–440 V 660 V–690 V	A	63 63
AC-15	Switching of control devices, contactors, valves etc.		220 V–240 V 380 V–440 V	A	16 7
Rated Utilization Category					
AC-2	Slip ring motor starting, reversing and plugging, star-delta starting	3 phase, 3 pole	220 V–240 V 380 V–440 V 500 V 660 V–690 V	kW	18,5 30 40 37
AC-3	Direct-on-line starting, star-delta starting	3 phase, 3 pole	220 V–240 V 380 V–440 V 500 V 660 V–690 V	kW	11 18,5 18,5 22
		1 phase, 2 pole	110 V–120 V 220 V–240 V 380 V–440 V	kW	3 6 11
AC-4	Direct-on-line starting, reversing, plugging and inching	3 phase, 3 pole	220 V–240 V 380 V–440 V 500 V 660 V–690 V	kW	5,5 7,5 7,5 9
		1 phase, 2 pole	110 V–120 V 220 V–240 V 380 V–440 V	kW	1,2 2,4 4
AC-23A	Frequent switching of motors or other high inductive loads	3 phase, 3 pole	220 V–240 V 380 V–440 V 500 V 660 V–690 V	kW	15 30 30 30
		1 phase, 2 pole	110 V–120 V 220 V–240 V 380 V–440 V	kW	4 10 18,5
Short Circuit Protection					
Max. fuse size		gG-characteristic		A	63
Rated short-time withstand current		(1 s-current)		A	950
Max. Permissible Wire Gage - copper wires only					
Single-core or stranded wire				mm ²	16
Flexible wire				mm ²	10
Flexible wire with sleeving in accordance with DIN 46228				mm ²	10

¹ Valid for lines with grounded common neutral termination, overvoltage category III, Other values on request.

Miscellaneous

Tightening torque of terminal screw:	1,8 Nm (16 lb-in)	
Minimum Voltage:	on request	
Power loss per contact at I_U :	2,8 W	
Resistance to vibration:	on request	
Resistance to shock:	min. 5 g, 30 ms	
Min. Ambient Temperature of Stages:	-5 °C	
Max. Ambient Temperature of Stages:	open at 100 % I_U/I_{th} enclosed at 100 % I_{the}	55 °C during 24 hours with peaks up to 60 °C 35 °C during 24 hours with peaks up to 40 °C
Storage temperature:	-40 °C to 85 °C (in case of temperature below -5°C no shock load permissible)	

Approvals and Standards

IEC 60947
EN 60947

cULUS

EAC

USA / Canada



Rated Thermal Current $I_U/I_{th}/I_{the}$				A	65
Rated Insulation Voltage U_i				V	600
Rated Operational Current I_e					
Pilot Duty				Heavy	VAC A600
Ampere Rating	Resistive or low inductive loads			A	60
Max. Permissible Wire Gage - copper wires only					
Single-core or stranded wire				AWG	6
Flexible wire: AWG wire (without sleeving)				AWG	6
Ratings					
	Standard motor load, DOL - Rating (similar AC-3)	3-phase 3-pole	110 V–120 V	HP	7,5
			220 V–240 V		15
			440 V–480 V		30
			550 V–600 V		30
		1-phase 2-pole	110 V–120 V	HP	3
			220 V–240 V		7,5
			277 V		10
			440 V–480 V		15
			550 V–600 V		20

Miscellaneous

Tightening torque of terminal screw:	1,8 Nm (16 lb-in)	
Minimum Voltage:	on request	
Power loss per contact at I_U :	2,8 W	
Resistance to vibration:	on request	
Resistance to shock:	min. 5 g, 30 ms	
Min. Ambient Temperature of Stages:	-5 °C	
Max. Ambient Temperature of Stages:	open at 100 % I_U/I_{th}	55 °C during 24 hours with peaks up to 60 °C
	enclosed at 100 % I_{the}	35 °C during 24 hours with peaks up to 40 °C
Storage temperature:	-40 °C to 85 °C (in case of temperature below -5°C no shock load permissible)	

Approvals and Standards

IEC 60947
EN 60947